PISTOL GRIP THREE POINTS BORE GAGE

Optional accessory: digital indicators (code 2103-10F, resolution 0.001mm/0.00005") or dial indicators (graduation 0.001mm), setting rings (code 6312)

setting ring extension rod



6-100mm: included 100-300mm: optional

+INSIZE+

included


Manufacturer Inspection Certificate

Inspection Certificate

Paulo







stem hole 3/8" with bush Ø8 Type A 6-12mm, steel digital indicator measuring points is not included 2124-8 Type B 12-50mm, carbide digital indicator measuring points is not included 2124-25



Unit: mm

102

Type C 50-300mm, carbide measuring points

digital indicator is not included 2124-125

Individual

(ľ	Ì	1	Ì	ĩ	1
٠,	١.					

Code	Range	Туре	Accuracy (without digital indicator)	Setting ring	Extension rod (included)	L	а	b	С
2124-8*	6-8mm	Α	4µm	Ø6mm(included)	100mm	50	1.5	2.5	_
2124-10 *	8-10mm	Α	4µm	Ø8mm(included)	100mm	50	1.5	2.5	_
2124-12 *	10-12mm	Α	4µm	Ø10mm(included)	100mm	50	1.5	2.5	_
2124-16*	12-16mm	В	4µm	Ø16mm(included)	150mm	65	0.5	6	4.5
2124-20 *	16-20mm	В	4µm	Ø16mm(included)	150mm	65	0.5	6	4.5
2124-25 *	20-25mm	В	4µm	Ø25mm(included)	150mm	91	0.5	8	6
2124-30 *	25-30mm	В	4µm	Ø25mm(included)	150mm	91	0.5	8	6
2124-40 *	30-40mm	В	4µm	Ø40mm(included)	150mm	97	0.5	14	12
2124-50 *	40-50mm	В	5µm	Ø40mm(included)	150mm	97	0.5	14	12
2124-63 *	50-63mm	С	5µm	Ø62mm(included)	150mm	112	0.5	17.5	14.5
2124-75 *	62-75mm	С	5µm	Ø62mm(included)	150mm	112	0.5	17.5	14.5
2124-88 *	75-88mm	С	5µm	Ø87mm(included)	150mm	112	0.5	17.5	14.5
2124-100*	87-100mm	С	5µm	Ø87mm(included)	150mm	112	0.5	17.5	14.5
2124-125*	100-125mm	С	5µm	Ø112.5mm(optional)	150mm	130	0.5	19.5	14.5
2124-150*	125-150mm	С	5µm	Ø137.5mm(optional)	150mm	130	0.5	19.5	14.5
2124-175*	150-175mm	С	5µm	Ø162.5mm(optional)	150mm	130	0.5	19.5	14.5
2124-200*	175-200mm	С	5µm	Ø187.5mm(optional)	150mm	130	0.5	19.5	14.5
2124-225	200-225mm	С	7µm	Ø212.5mm(optional)	150mm	130	0.5	19.5	14.5
2124-250	225-250mm	С	7µm	Ø237.5mm(optional)	150mm	130	0.5	19.5	14.5
2124-275	250-275mm	С	7µm	Ø262.5mm(optional)	150mm	130	0.5	19.5	14.5
2124-300	275-300mm	С	7µm	Ø287.5mm(optional)	150mm	130	0.5	19.5	14.5

Set

Code	Range	Probes included	Setting ring (included)	Extension rod (included)
2124-S123*	6-12mm	6-8mm, 8-10mm, 10-12mm	Ø6mm, Ø8mm, Ø10mm	100mm
2124-S202*	12-20mm	12-16mm, 16-20mm	Ø16mm	150mm
2124-S504 *	20-50mm	20-25mm, 25-30mm, 30-40mm, 40-50mm	Ø25mm, Ø40mm	150mm
2124-S1004*	50-100mm	50-63mm, 62-75mm, 75-88mm, 87-100mm	Ø62mm, Ø87mm	150mm



