



# SPLIT TYPE DIAL BORE GAGE SET FOR BLIND HOLES


(mm)

Code	Range	Quantity of points	Measuring range of point	Measuring depth (L1)	Total length (L)	Setting ring (optional)	
						Code	Diameter
2429-4	1.5-4.2	10	1.5 - 1.9	17	93	6312-1D75	1.75
			1.8 - 2.2	17	93	6312-2	2
			2.05 - 2.45	17	93	6312-2D25	2.25
			2.3 - 2.7	25	101	6312-2D5	2.5
			2.55 - 2.95	25	101	6312-2D75	2.75
			2.8 - 3.2	25	101	6312-3	3
			3.05 - 3.45	25	101	6312-3D25	3.25
			3.3 - 3.7	25	101	6312-3D5	3.5
			3.55 - 3.95	25	101	6312-3D75	3.75
			3.8 - 4.2	25	101	6312-4	4
2429-7D5	4.15-7.8	7	4.15 - 4.8	41	118	6312-4D5	4.5
			4.7 - 5.3	41	118	6312-5	5
			5.2 - 5.8	41	118	6312-5D5	5.5
			5.7 - 6.3	41	118	6312-6	6
			6.2 - 6.8	41	118	6312-6D5	6.5
			6.7 - 7.3	41	118	6312-7	7
			7.2 - 7.8	45	118	6312-7D5	7.5
2429-12	7.7-12.5	6	7.7 - 8.3	45	118	6312-8	8
			8.2 - 8.8	45	118	6312-8D5	8.5
			8.7 - 9.3	45	118	6312-9	9
			9.2 - 10.5	45	118	6312-10	10
			10.2 - 11.5	45	118	6312-11	11
			11.2 - 12.5	45	118	6312-12	12
2429-20	12.2-20.6	8	12.2 - 13.5	45	118	6312-13	13
			13.4 - 14.6	45	118	6312-14	14
			14.4 - 15.6	45	118	6312-15	15
			15.4 - 16.6	45	118	6312-16	16
			16.4 - 17.6	45	118	6312-17	17
			17.4 - 18.6	45	118	6312-18	18
			18.4 - 19.6	45	118	6312-19	19
			19.4 - 20.6	45	118	6312-20	20



2429-4

dial indicator is not included



- Split type contact points
- Accuracy (without indicator):  
3µm (measuring range 1.5~10mm),  
4µm (measuring range 10~20.6mm)
- Repeatability (without indicator): 1µm
- Setting rings and dial indicators are optional