


- To measure large external or internal diameters
- Automatic judgment and display external or internal diameter
- Titanium arm, light in weight
- Backlight LCD display, can rotate 180 ° for easy reading
- Memory of 12 readings and average calculation
- With minimum and maximum measurement mode
- Angle can be displayed



external diameter measurement



internal diameter measurement



SPECIFICATION

Range	external	Ø500~6000mm/19.69~236.22"	
	internal	Ø1100~6000mm/43.31~236.22"	
Resolution		0.01mm/0.001"	
Accuracy		±(0.01+D²/30)mm (D is the diameter to be measured, in meter)	
Power supply		rechargeable battery (for 8 hours working)	
Weight		3.8kg	

STANDARD DELIVERY

Main unit	1pc
AC/DC adapter	1pc
USB cable and software	1pc

display of angle

0 0	0 0	
	profits took profit on onknown relet	
F00K07K050000	100	
1 Silding	(1)	2496131
2 AVENUE		34MESS!
a 7013644		4457 PARRIED :-
g 752.95.44	(8)	0.000 NO
a worke	44	9 MONE 9001 - 28 C SE.
0	iii.	WANTED STREET

software (included), data output, save and print

Accuracy sample by diameters

Accuracy sample by diameters				
Diameter	Accuracy			
500mm	±0.018mm			
1000mm	±0.043mm			
1500mm	±0.085mm			
2000mm	±0.143mm			
2500mm	±0.218mm			
3000mm	±0.310mm			
4000mm	±0.543mm			
5000mm	±0.843mm			
6000mm	±1.210mm			