


CUSTOM-MADE

OTHER CLASSES ARE AVAILABLE, SUCH AS H8, H9
OTHER DIAMETERS ARE AVAILABLE, SUCH AS 19.003mm
OTHER LENGTHS ARE AVAILABLE, SUCH AS 70mm

- Supplied with Go and No-Go gages together
- Class H7
- Hardness HRC 60±2
- Standard DIN7150-2

PLAIN PLUG GAGE



4124-12

Size tolerance of H7

(mm)


Diameter Ød (mm)	Size tolerance of Go gage	Size tolerance of No-Go gage	L1	L2	L	S1, S2
≥2, ≤3	+0.0010 / +0.0022	+0.0088 / +0.010	6.5	4.5	20	—
>3, ≤6	+0.0013 / +0.0027	+0.0106 / +0.012	8	6	24	—
>6, ≤10	+0.0015 / +0.0033	+0.0132 / +0.015	10	7	29	—
>10, ≤14	+0.0018 / +0.0038	+0.0160 / +0.018	12	8	34	—
>14, ≤18	+0.0018 / +0.0038	+0.0160 / +0.018	14	10	36	—
>18, ≤24	+0.0023 / +0.0046	+0.0186 / +0.021	16	12	42	—
>24, ≤30	+0.0023 / +0.0046	+0.0186 / +0.021	18	14	42	—
>30, ≤40	+0.0023 / +0.0055	+0.0220 / +0.025	20	15	55	—
>40, ≤50	+0.0023 / +0.0055	+0.0220 / +0.025	25	18	60	—
>50, ≤65	+0.0028 / +0.0064	+0.0264 / +0.030	30	18	—	164, 152
>65, ≤80	+0.0028 / +0.0064	+0.0264 / +0.030	35	25	—	169, 159
>80, ≤100	+0.0032 / +0.0075	+0.0308 / +0.035	35	25	—	169, 159

Type A



Type A

Type B



Type B

Code	Diameter (mm)	Type
4124-2	2	A
4124-3	3	A
4124-4	4	A
4124-5	5	A
4124-6	6	A
4124-7	7	A
4124-8	8	A
4124-9	9	A
4124-10	10	A
4124-11	11	A
4124-12	12	A
4124-13	13	A
4124-14	14	A
4124-15	15	A
4124-16	16	A

Code	Diameter (mm)	Type
4124-17	17	A
4124-18	18	A
4124-19	19	A
4124-20	20	A
4124-21	21	A
4124-22	22	A
4124-23	23	A
4124-24	24	A
4124-25	25	A
4124-26	26	A
4124-27	27	A
4124-28	28	A
4124-29	29	A
4124-30	30	A
4124-31	31	A

Code	Diameter (mm)	Type
4124-32	32	A
4124-33	33	A
4124-34	34	A
4124-35	35	A
4124-36	36	A
4124-37	37	A
4124-38	38	A
4124-39	39	A
4124-40	40	A
4124-41	41	A
4124-42	42	A
4124-43	43	A
4124-44	44	A
4124-45	45	A
4124-46	46	A

Code	Diameter (mm)	Type
4124-47	47	A
4124-48	48	A
4124-49	49	A
4124-50	50	A
4124-52	52	B
4124-55	55	B
4124-60	60	B
4124-65	65	B
4124-70	70	B
4124-75	75	B
4124-80	80	B
4124-85	85	B
4124-90	90	B
4124-95	95	B
4124-100	100	B