

METRIC FINE THREAD PLUG GAGE



4642-12R

- Class 6H
- Standard ISO1502
- Material: OHNS
(Oil Hardened Non-shrinking Steel),
stable dimension and wear resistance
- Hardness HRC60-62

Code	Size (mm)	Code	Size (mm)	Code	Size (mm)	Code	Size (mm)	Code	Size (mm)
4642-8G*	M8x0.5	4642-14R*	M14x1.5	4642-25R*	M25x1.5	4642-35R*	M35x1.5	4642-48T*	M48x2
4642-8L*	M8x0.75	4642-16P*	M16x1	4642-26R*	M26x1.5	4642-36R*	M36x1.5	4642-50R*	M50x1.5
4642-8P*	M8x1	4642-16R*	M16x1.5	4642-27R*	M27x1.5	4642-36T*	M36x2	4642-50T*	M50x2
4642-10L*	M10x0.75	4642-18P*	M18x1	4642-27T*	M27x2	4642-38R*	M38x1.5	4642-52R*	M52x1.5
4642-10P*	M10x1	4642-18R*	M18x1.5	4642-28R*	M28x1.5	4642-40R*	M40x1.5	4642-52T*	M52x2
4642-10Q*	M10x1.25	4642-20P*	M20x1	4642-30P*	M30x1	4642-40T*	M40x2	4642-55R*	M55x1.5
4642-12P*	M12x1	4642-20R*	M20x1.5	4642-30R*	M30x1.5	4642-42R*	M42x1.5	4642-55T*	M55x2
4642-12Q*	M12x1.25	4642-22R*	M22x1.5	4642-30T*	M30x2	4642-42T*	M42x2	4642-58R*	M58x1.5
4642-12R*	M12x1.5	4642-24P*	M24x1	4642-32R*	M32x1.5	4642-45R*	M45x1.5	4642-60T*	M60x2
4642-14P*	M14x1	4642-24R*	M24x1.5	4642-33R*	M33x1.5	4642-45T*	M45x2		
4642-14Q*	M14x1.25	4642-24T*	M24x2	4642-33T*	M33x2	4642-48R*	M48x1.5		

* Supplied with manufacturer inspection certificate