


LINEAR GAGE
IP65
 WATERPROOF




INTERFACE BOX SPECIFICATION

| Code | 7107-1 | 7107-2 |
|--|-----------------|--------|
| Quantity of linear gages to be connected | 4pcs | 8pcs |
| Data port | RS232 and RS485 | |
| Power supply | DC 9~24V | |



linear gage



- Software is supplied with interface boxes. In the software, it is possible to set tolerance of each channel and show judgment (red when out of tolerance, green when within tolerance), set zero, collect data manually or automatically (time is adjustable), output data to Excel, print report


LINEAR GAGE SPECIFICATION

| Code | 7107-11 | 7107-12 |
|---------------------|-------------------|---------|
| Measuring range | 12mm | 12mm |
| Resolution | 0.01mm | 0.001mm |
| Accuracy | 20μm | 5μm |
| Hysteresis | 10μm | 2μm |
| Measuring principle | capacity system | |
| Voltage | 5V | |
| Sampling frequency | 100 times/sec. | |
| Working life | ten million times | |
| Dust/waterproof | IP65 | |
| Measuring force | 1.5N | |
| Cable length | 2m | |
| Data output | RS232 | |

MULTI LINEAR GAGE SYSTEM



4-channel interface box
7107-1



8-channel interface box
7107-2

