

# PROFILE PROJECTOR

Screen diameter: 300mm

X-Y travel: 150x50mm



ISP-Z3015



ISP-A1000E

digital readout of ISP-A1000E

- touch buttons
- USB data output to Excel and CAD
- show diagram directly

## OPTIONAL ACCESSORY



lens



rotary table  
(glass plate diameter 100mm)



overlay chart (protractor with 1°  
graduation, radius with 1mm increment)



holder with clamp



swivel center support




V-block with clamp



50mm reading scale  
(check magnification accuracy)



300mm calibration scale (check  
magnification accuracy together  
with 50mm reading scale or  
calibrate measuring accuracy)



blue filter



demo sample

















printer (only for ISP-A1000E)

To be continued

Continued from previous page

## SPECIFICATION

Code		ISP-Z3015		ISP-A1000E		
Edge detector		not included		included		
Lens	magnification	10X (included)	20X (optional)	50X (optional)	100X (optional)	
	view field	Ø30mm	Ø15mm	Ø6mm	Ø3mm	
	working distance	77.7mm	44.3mm	38.4mm	25.3mm	
Max. workpiece height		90mm	90mm	90mm	90mm	
Magnification accuracy		±0.08%				
Image		erect image				
Projector screen		diameter: Ø300mm				
		rotation range: 0°~360°, resolution: 1" or 0.01°				
		reference lines: cross-hairs				
Stage	metal stage size	340×152mm				
	glass stage size	196×96mm				
	X-Y stage travel	range: 150×50mm				
		resolution: 0.5µm				
	Z (focus) travel range	90mm				
max. load capacity	4kg					
Illumination		contour illumination: 24V/150W halogen lamp, brightness is adjustable				
		surface illumination: 24V/150W halogen lamp				
Data processing unit	display	X-Y stage travel, screen rotation				
	output	RS232C		RS232C, USB (data output to Excel and CAD)		
	function		measure coordinate of point		 measure coordinate of point	
			measure coordinate of line		 measure coordinate of line	
			measure center coordinate, radius of circle with three points		 measure center coordinate, radius of circle with three points	
		measure distance between two objects		 measure distance between two objects		
		measure angle with four points or two lines		 measure angle with four points or two lines		
		set origin of coordinate		 coordinate transform		
		coordinate transform		 choose measurement object automatically according to the selective point and display the result		
advanced function	—		Programming for batch measurements			
Power supply		110/220V, 50/60Hz				
Dimension (L×W×H)		550×770×1100mm				
Weight		135kg				

## STANDARD DELIVERY

Main unit	1pc
10X lens with half-reflection mirror and oblique illuminator mirror	1pc
Overlay chart clip	4pcs
Foot-switch	1pc
Anti-dust cover	1pc
USB cable and software (only for ISP-A1000E)	1pc

## OPTIONAL ACCESSORY

20X lens with half-reflection mirror and oblique illuminator mirror	ISP-Z3015-LENS20X	Swivel center support	ISP-Z3015-SUPPORT
50X lens with half-reflection mirror	ISP-Z3015-LENS50X	V-block with clamp	ISP-Z3015-VBLOCK
100X lens with half-reflection mirror	ISP-Z3015-LENS100X	50mm reading scale	ISP-Z3015-SCALE50
Rotary table	ISP-Z3015-TABLE	300mm calibration scale	ISP-Z3015-RULE
Overlay chart	ISP-Z3015-CHART	Blue filter	ISP-Z3015-FILTER
Holder with clamp	ISP-Z3015-HOLDER	Demo sample	ISP-Z3015-DEMO
		Printer (only for ISP-A1000E)	ISP-A1000-PRINTER