

# DIGITAL ANGLE TORQUE WRENCH

- Clockwise and counter-clockwise operation
- Set the desired torque first. After reaching the desired torque, set the angle and turn the wrench at this angle to apply extra torque
- Unit: N.m, in.lb, ft.lb, kg.cm, degree
- Peak and track working mode
- Target torque or angle value can be set, with audible and visible alarm:
  - Green LED light on and buzzer sounds when torque or angle value is 90%~100% of target torque or angle
  - Both green and red LED light on and buzzer sounds when target torque or angle value is reached
- Power off in 5 minutes automatically
- Non-slip grip handle
- With damp record
- With overload record (once the torque reaches 110% of the maximum range)



IST-1W135A

## SPECIFICATION

Code		IST-1W30A	IST-1W135A	IST-1W200A	IST-1W340A
Range	torque	6~30N.m	27~135N.m	40~200N.m	68~340N.m
	angle	0~999°			
Accuracy	clockwise	±2%			
	counter-clockwise	±3%			
	angle	±2° (rotate 90°)			
Resolution	torque	0.01N.m	0.1N.m	0.1N.m	0.1N.m
	angle	1°			
Square driver (L)		1/4"	3/8"	1/2"	1/2"
Power supply		2xAA batteries, for 110 hours working			
Length		390mm	415mm	530mm	650mm
Weight		830g	950g	1400g	1600g

## OPTIONAL ACCESSORY

Calibration cable	IST-W-CABLE
-------------------	-------------



Set the desired torque first. After reaching the desired torque, set the angle and turn the wrench at this angle to apply extra torque